

# Technical Specifications

<b>Model t557k</b>	<b>PC144A</b>
<b>Processor &amp; Speed</b>	3.0 GHz/800 Intel® Pentium® 4(P) Processor – PGA478
<b>Chipset</b>	Intel® 848P
<b>Motherboard</b>	Oxford-UL6E (4PSD-LA)
<b>RAM</b>	512/2700 MB 333 DDR SDRAM
Maximum	2 GB (2x1024MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 AND 1024 MB DDR DIMMs
<b>Free DIMM Sockets</b>	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
<b>Cache</b>	16KB Data Cache + Trace Cache L1, 1MB L2 Integrated on Processor module
<b>Hard Drive</b>	80 GB (7200 RPM)
<b>CD-ROM Drive</b>	CD-ROM Drive: 48x maximum speed
Access Speed	75ms
Transfer Rate	7.2 MB/sec
<b>Diskette Drive</b>	3.5" (1.44MB)
<b>Video Graphics</b>	AGP 8X Graphics Card
Controller	nVidia FX5700
Video Memory	256 MB DDR, not upgradeable
Video Connectors	Composite & S-Video - NTSC
<b>Network Card</b>	10/100 BaseT, Integrated
<b>1394 Card</b>	IEEE-1394, Integrated
<b>Sound</b>	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650
<b>Chassis</b>	Jaguar, 250HV PSU
<b>USB Interface Specification</b>	USB 2.0
<b>External I/O</b> Rear Connectors	4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone
<b>External I/O</b> Front Connectors	2=USB;1= 1394, Line In, Microphone, Headphone
<b>Expansion Slots (Total)</b>	3= PCI, 1= AGP
<b>Expansion Slots (FREE)</b>	3= PCI
<b>Drive Bays (Total)</b>	Two 5.25" external, One 3.5" external, Two 3.5" internal
<b>Drive Bays (FREE)</b>	One 5.25" external, One 3.5" external, One 3.5" internal
<b>Keyboard/Mouse</b>	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

---

Copyright Hewlett-Packard Co. 1994-2004  
This information is subject to change without notice and  
is provided "as is" with no warranty.  
Hewlett-Packard shall not be liable for any direct,  
indirect, special, incidental or consequential damages  
in connection with the use of this material.